SEA PIXEL NEXT ELECTRONIC SORTING





CONVEYING | DRYING | SEED PROCESSING | ELECTRONIC SORTING | STORAGE | TURNKEY



PROGRESS NEEDS PASSION FOR DETAILS

Next

STATE-OF-THE-ART TECHNOLOGY

Many years of experience has made SEA a leading player grain in electronic sorting technology. When it comes to optimizing the crop qualities by sorting the grain and seed, the strong market position is a result of 40 years of knowhow within development and production of optical electronic colour sorting equipment. This enables us to offer innovative and flexible sorting solutions based on a technical experience and a strong concept.

We offer the SEA Pixel Next colour sorter series, a result of state-of-the-art technology where traditional advantages have been improved with most advanced technology, whilst maintaining simplicity of use.

WORKING PROCESS



OPERATION

- 1 Input product is loaded into the in-feed hopper,
- 2 it moves along the vibrating plate
- 3 until it flows on to a sloping chute where it is individually checked and sorted by state-of-the-art cameras
- 4 (CCD cameras for standard version and
- 5 additional cameras for bichromatic, NIR and InGaAs versions) situated in the front and rear of the flow.
- 6 Depending on the signals received by the optical device, the sorter software controls the pneumatic device
- 7 which physically separates the unwanted products out of the conforming ones which naturally reach their discharging hopper.
- 8 The rejected products are instead deviated by a jet of compressed air produced by the relevant ejector and discharged in the front side hopper.


In automatic re-pass versions, the sorted or rejected product is automatically conveyed to another section of the machine to undergo an identical process.







MODEL	NEXT 1	NEXT 1,5	NEXT 2	NEXT 3	NEXT 4	NEXT 5	NEXT 6	NEXT 7
CONFIGURATION								
VIBRATOR	1	2	2	3	4	5	6	7
CHUTE	1	2	2	3	4	5	6	7
CCD CAMERAS*	2	2	4	6	8	10	12	14
EJECTORS	54	77	108	162	216	270	324	378



* Data referred to monochromatic configurations. It is possible to configure any model into bi-chromatic, NIR and InGaAs versions depending on different sorting requirements.

MODEL		NEXT 1	NEXT 1.5	NEXT 2	NEXT 3	NEXT 4	NEXT 5	NEXT 6	NEXT 7
		NEXT	NEXT 1,5	NEXT 2	NEXT 0	NEXT 4	NEXT 5	NEXTO	NEXT 7
DIMENSIONS	mm								
WIDTH		1560	920	1560	1560	1950	1950	2540	2540
DEPTH		1550	1715	1550	1550	1550	1550	1550	1550
HEIGHT		2100	2100	2100	2100	2100	2100	2100	2100
POWER CONS.	kW	1,0	1,0	1,5	1,5	2,5	2,5	3,0	3,0
AIR CONS AT 4 BAR	l/sec	8,4	12,6	16,8	25,2	33,6	42,0	50,4	58,8

The dimensions and technical data herein mentioned are only indicative and they can be subject to changes. SEA s.r.l. reserves the right to change them at any time without prior notice.







MACHINE RANGE

















MAIN FEATURES

• UP TO 7 CHUTES

To satisfy even the highest production capacities.

VERSATILE CONFIGURATION

Multiple and resort sorting passes set up; Flexible and user-friendly adjust and programming.

LED RGB LIGHTING AND BACKGROUND

Full colour RGB Led, exclusively designed for SEA, in association with one leader producer, allows the most precise focusing of the beam on the inspection line; Long lasting and reliability (over 100.000 h) and low heat dissipation.

UP TO 28 CAMERAS FOR ANY KIND OF OPTICAL CONFIGURATION

Up to 4 cameras per chute for monochrome, bi-chrome, NIR and InGaAs configurations, and with size control; 2048 Pixel CCD cameras allow the highest optical resolution for camera / inspection surface ratio (0.1 mm); The optical system grants extreme flexibility in image processing, allowing the sorter sensitivity setting based on colour/transparency and dimension of the defects to separate;

Pixel Next CCD cameras have best possible signal/noise ratio.

• ELECTRONICS - HARDWARE

Hardware organized in easily replaceable electronic boards, using the ultimate SMD and FBGA technology; Self-control functions, such as auto-diagnosis and auto-calibration;

Back-up of the operating software by USB on board. The high speed signal elaboration and communication to expulsion system allows an excellent performance.

EJECTION SYSTEM

State-of-the-art ejectors guarantee most accurate precision and expulsion rapidity, producing highly concentrated rejects; Extremely fast ejectors are guaranteed for over 2 billion operating cycles and they can easily be repaired or replaced; Blowers directly placed on the ejectors pneumatic lung.

NEW 15 INCHES COLOUR TOUCH-SCREEN DISPLAY

The Windows XP embedded graphic interface assures an easy connection to company networks and to remote assistance systems.

MECHANICAL DESIGN

Pressurized and conditioned optical boxes; Airtight structure prevents dust and product outflow; Easy product sampling collection; The folding optical boxes enable the full opening of the sorter, facilitating its cleaning and maintenance; Pixel Next sorters are provided with standard flanges for de-dusting systems; additional pre-arrangement for aspiration system available as option.

RELIABILTY

Remote control and on-line assistance from SEA headquarters; Prompt technical interventions on site; Programmed technical service contracts; Servicing and spare parts centers in several Countries; Best references in the international markets.

• OTHER

CE certification of conformity can be combined with ATEX 22 certification (option) Customized color (option) Stainless steel (AISI 316L) version available (option)



NEW 15 INCHES COLOUR TOUCH-SCREEN DISPLAY

APPLICATIONS

SORTED

Wheat

Rice

REJECTED

SORTED

Pine nuts

Pistachios

Almonds

Salt

Minerals

PET

Best optical resolution - Minimum rejects - High production capacities






Maize









Onion seeds



Sunflower seeds





Chickpeas



Fava beans



Roasted Coffee



Green Coffee










PVC window prof.



hdPE



Plastic granules

	122533	North Press	
5 6 m A 10	(SSEP)		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	COLOR:		
	12253		

Testing units available at SEA headquarters for free of charge tests.



A/S CIMBRIA

Cimbria House Faartoftvej 22 P.O. Box 40, 7700 Thisted DENMARK Phone: +45 96 17 90 00 holding@cimbria.com www.cimbria.com

SEA S.R.L.

Via Colombarotto 2 40026 Imola BO ITALY Phone: +39 0542 361423 info@seasort.com www.seasort.com

SOLUTIONS. TOGETHER.

nhouse 10.12